



## Equipment For Sale: MAB 103B-24

### Equipment Specifications

- MAB 103 as is; needs rebuilt w/ bearings, seals, drive clutch and fitting
- Fluid Processing Rate:  
- 1.0 to 4.0 GPM oil
- Stainless steel bowl, disc and feed hardware
- Power Consumption:  
idling - 0.4 kW  
running (max. cap.) - 0.6 kW
- Motor: 4-pole 0.75 kW  
3-phase 60 Hz
- Bowl Speed: 8,600 RPM
- Weight:: 220 pound

The MAB 103B-24 is a high-speed, manual cleaned centrifugal separator intended for industrial oil applications. It is specially designed for purifying/clarifying fuel oil, lubricating oils and hydraulic fluids.

The sludge may consist of a mixture of water, oil, and solids. The clean oil (light phase) is discharged using a pump and the water based fluid (heavy phase) is discharged continuously using gravity. The solid particles are removed when the bowl is cleaned.

The separator has to be installed together with devices for control of its operation.



### INDUSTRIAL FLUID SYSTEMS

22200 Ryan Road  
Warren, MI 48091

Phone: 800-343-8106

Fax: 586-754-8284

[www.industrialfluidsystems.com](http://www.industrialfluidsystems.com)

**Serial No: 881145-09-01**