



Ultra Vac Model: UV-10

Standard Features

- 600 GPH Process Flow Rate
- 24kW Heater w/ Programmable Temperature Controller
- Dry Seal Vacuum Pump w/ Oil Sump
- Electrical Controls w/ "On" indicator, alarm lights and phase monitor
- 440V-3Ph-60Hz Power
- Adjustable Flow Control
- W32"x L40"x H66"
- 984 lbs
- Sample Ports
- Pressure Gauge
- Non-Re-settable Hour Meter
- Parker Filter Assembly
- Parker Filter Element
- 6" Caster Wheels
- 25' Electrical Cord
- One Year Warranty
- Operational & Maintenance Manual w/ Spare Parts List

Safety Features

- High Temp Shutdown Circuit
- High Oil Level Shutdown
- High Condensate Tank Shutdown

Standard Options

- Fork Lift Pockets
- Inlet & Outlet Hoses
- PLC Control Screen
- Feed Shutoff Valve
- Flow Meter
- Auto Condensate Drain

The UV-10 vacuum dehydration unit is capable of removing water from most lubricating, EHC and hydraulic fluids. It is designed for 1,000 - 1,500 gallon systems. This machine will process fluid at a rate of 600 gallons per hour and is capable of reducing water levels to less than 150 ppm. Options and custom modifications are available.



INDUSTRIAL FLUID SYSTEMS

22200 Ryan Road
Warren, MI 48091

Phone: 800-343-8106

Fax: 586-754-8284

www.industrialfluidsystems.com