



INDUSTRIAL FLUID SYSTEMS

Ultra Vac Model: UV-15

Standard Features

- 900 GPH Process Flow Rate
- 24kW Heater w/ Programmable Temperature Controller
- Dry Seal Vacuum Pump w/ Oil Sump
- Electrical Controls w/ "On" indicator, alarm lights and phase monitor
- 440V- 3Ph- 60Hz Power
- W32" x L56" x H60"
- Adjustable Flow Control
- 1150 lbs.
- Sample Ports
- Pressure Gauge
- Non-Re-settable Hour Meter
- Parker Filter Assembly
- Parker Filter Element
- 6" Caster Wheels
- 25' Electrical Cord
- One Year Warranty
- Operational & Maintenance Manual w/ Spare Parts List

Safety Features

- High Temp Shutdown Circuit
- High Oil Level Shutdown
- High Condensate Tank Shutdown

Standard Options

- Fork Lift Pockets
- Inlet & Outlet Hoses
- PLC Control Screen
- Dirty Filter Light
- Feed Shutoff Valve
- Flow Meter
- Auto Condensate Drain

The UV-15 vacuum dehydration unit is capable of removing water from most lubricating, EHC and hydraulic fluids. It is designed for 1,100 - 2,500 gallon systems. This machine will process fluid at a rate of 900 gallons per hour and is capable of reducing water levels to less than 150 ppm. Options and custom modifications are available.



**INDUSTRIAL FLUID
SYSTEMS**

22200 Ryan Road
Warren, MI 48091

Phone: 800-343-8106

Fax: 586-754-8284

www.industrialfluidsystems.com